

PRODUCT NO. 1730-1

DOTLUX LED tube LUMENPLUS 90cm 10W flesh color frosted rotatable end cap



to the product page

- SPECIAL LIGHT FOR BUTCHER'S COUNTERS
- Shatterproof polycarbonate cover
- Double savings: Electricity for light and cooling!
- No heat load on the goods, which significantly reduces cut and product losses
- Prevents condensation forming in blister packs of fresh produce
- Special red tones in the LED make meat and sausage products look fresh
- This LED light is suitable for use in food processing companies.
- It can therefore also be used in areas that are certified in accordance with the International Featured Standard (IFS) or British Retail Consortium (BRC).

PRODUCT GROUP	EC001959_LED-Lampe/Multi-LED		
SUCCESSION ARTICLE	-	BEAM ANGLE	180
WEIGHT IN KG	0.19	DIMMABLE	No
POWER CONSUMPTION IN WATTS	10	PROTECTION CLASS (IP)	IP20
NET LUMINOUS FLUX IN LUMENS	1060	INPUT VOLTAGE	176 - 240 AC/DC
LUMEN PER WATT	106	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	-
		COLOR-RENDERING-INDEX	CRI > 85
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	106
Dimensions		VOLTAGE TYPE	AC/DC
length: 895mm		HOUSING COLOUR	colourless
width: 26mm		SUITED FOR EMERGENCY LIGHTING	yes
height: 26mm		SWITCH CYCLES	> 100.000
diameter: 26mm		WARRANTY IN YEARS	5
		L80/B10	50000
		DIMMING WITHOUT DIMMER	No
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	-
		LIFETIME L80/B10 AT 25°C	50000
		DIMMING TOUCH AND DIM	No
		DIMMING ZIGBEE	No
		NO DIM FUNCTION	Yes

COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
SUITABLE FOR EMERGENCY LIGHTING	Yes
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
LAMP SHAPE	Tube, double-ended
REMOTE OPERATION POSSIBLE	No
DIMMING PHASE CUT-ON	No
WITH REMOTE CONTROL	No
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	F
ELDAS-NR.	941801179
DIAMETER IN MM	26
LUMINOUS FLUX IN LM	1060
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-40
ABMESSUNGEN BREITE MM	26
ABMESSUNGEN HÖHE MM	26
NOMINAL VOLTAGE IN V	230
BEAM ANGLE	180
TYPE OF GLASS/COVER	Opal
COLOUR	White