

PRODUCT NO. 1940-1

DOTLUX LED tube LUMENPLUS 150cm 18W flesh color frosted rotatable end cap



to the product page

- SPECIAL LIGHT FOR BUTCHER'S COUNTERS
- Shatterproof polycarbonate cover
- Double savings: Electricity for light and cooling!
- No heat load on the goods, which significantly reduces cut and product losses
- Prevents condensation forming in blister packs of fresh produce
- Special red tones in the LED make meat and sausage products look fresh
- This LED light is suitable for use in food processing companies.
- It can therefore also be used in areas that are certified in accordance with the International Featured Standard (IFS) or British Retail Consortium (BRC).

PRODUCT GROUP EC001959_LED-Lampe/Multi-LED

SUCCESSION ARTICLE -

WEIGHT IN KG 0.32
POWER CONSUMPTION IN WATTS 18
NET LUMINOUS FLUX IN LUMENS 1900
LUMEN PER WATT 106

Dimensions

length: 1500mm
width: 26mm
height: 26mm
diameter: 26mm

BEAM ANGLE 180
DIMMABLE No
PROTECTION CLASS (IP) IP20
INPUT VOLTAGE 176 - 240 AC/DC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN -
COLOR-RENDERING-INDEX CRI > 85
CONSTRUCTION other
POWER FACTOR 0,95
INRUSH CURRENT IN A 0
LUMEN PER WATT 106
VOLTAGE TYPE AC/DC
HOUSING COLOUR colourless
SWITCH CYCLES > 100.000
WARRANTY IN YEARS 5
L80/B10 50000
DIMMING WITHOUT DIMMER No
ASSORTMENT Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 -
LIFETIME L80/B10 AT 25°C 50000
DIMMING TOUCH AND DIM No
DIMMING ZIGBEE No
NO DIM FUNCTION Yes

COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
LAMP SHAPE	Tube, double-ended
REMOTE OPERATION POSSIBLE	No
DIMMING PHASE CUT-ON WITH REMOTE CONTROL	No
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	F
ELDAS-NR.	941801199
Dimension Length in mm	
DIAMETER IN MM	26
LUMINOUS FLUX IN LM	1900
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-40
ABMESSUNGEN BREITE MM	26
ABMESSUNGEN HÖHE MM	26
NOMINAL VOLTAGE IN V	230
TYPE OF GLASS/COVER	Opal
COLOUR	White
LAMP DESIGNATION	Other