

PRODUCT NO. 2995

**DOTLUX Driver not dimmable 3W Suitable only for item no.: 2775**



to the product page

- Glare-free luminaire design especially for hotels and restaurants
- Driver and module can be replaced individually with lockable quick plug-in connection
- Maintenance-friendly, modular system components
- Natural color perception thanks to the extra high CRI value > 92

**PRODUCT GROUP** EC002710\_LED-Betriebsgerät

**SUCCESSION ARTICLE** -

**WEIGHT IN KG** 0.03

**POWER CONSUMPTION IN WATTS** 3

**Dimensions**

**length:** 74mm

**width:** 38mm

**height:** 25mm

<b>PROTECTION CLASS (IP)</b>	IP20
<b>INPUT VOLTAGE</b>	176 - 240 AC/DC
<b>POWER FACTOR</b>	0,5
<b>INRUSH CURRENT IN A</b>	0
<b>PROTECTION CLASS</b>	II
<b>SUITED FOR EMERGENCY LIGHTING</b>	yes
<b>OUTPUT VOLTAGE</b>	32 DC
<b>INPUT VOLTAGE SPAN</b>	180-250 V AC
<b>WARRANTY IN YEARS</b>	3
<b>DIMMING WITHOUT DIMMER</b>	No
<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	180-250 V AC
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No

<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	No
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>MODEL</b>	-
<b>SUITABLE FOR CONSTANT VOLTAGE</b>	No
<b>SUITABLE FOR OUTDOOR USE</b>	No
<b>SUITABLE FOR CONSTANT CURRENT</b>	Yes
<b>HOUSING</b>	Plastic housing
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ELDAS-NR.</b>	941934009
Dimension Length in mm	
<b>DIAMETER IN MM</b>	0
<b>RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C</b>	-20-+40
<b>ABMESSUNGEN BREITE MM</b>	38
<b>ABMESSUNGEN HÖHE MM</b>	25
Ausgangsstrom in A	
<b>MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16</b>	-
<b>MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16</b>	-