

DOTLUX LED street lamp RETROFIT E40 33W 3000K rotatable base

Order number: 2672-030200

- Optimally arranged LEDs enable uniform light distribution
- Light control through rotatable base (with latching function)
- Light efficiency of up to 150 lm / W due to the use of high-quality certified LEDs
- A low beam angle of approx. 200° optimizes the use in residential areas

Power consumption in watts: 33; Net luminous flux in lumens: 5150; Lumen per watt: 156; Beam angle: 200°; protection class (IP): IP40; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: approx. 35.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 80; Inrush current in A: 0; Lumen per watt: 156; Housing colour: white; Suited for emergency lighting: yes; Switch cycles: > 100.000; Input voltage span: 85-265 V AC / 140-387 V DC; Warranty in years: 5; L80/B10: 34000; Input voltage range luminaire: 85-265 V AC / 140-387 V DC; Energy efficiency class according to EU regulation 2019/2015: D; Lifetime L80/B10 at 25°C: 34000; LED-Lifetime light source L70/B50 at 25°C: 68000; ETIM Gruppen-ID: EC000062; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Suitable for emergency lighting: Yes; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 68000; Lifetime L90/B10 at 25°C: 17000; Pulse duration in µs: 0; Lifetime L90/B50 at 25°C: 22667; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Material cover: Without cover diameter: 90mm