

DOTLUX LED strip 48W 10mm 5000K IP66 5m roll incl. 50cm connection cable on both sides

Order number: 3943-050IP665M

- Comfortable and natural light due to extra high color rendering RA>92.
- Uniform color temperature due to 3-Step Mac Adam Binning and specially extruded IP66 protective cover
- Very densely arranged LEDs allow homogeneous illuminated areas at smallest distances
- Secure Solder Connect Technology prevents hairline cracks and cold solder joints
- Reinforced conductor paths ensure uniform brightness
- Original 3M adhesive tape provides strong hold
- 15 cm connection cable pre-mounted on one side

Power consumption in watts: 48; Net luminous flux in lumens: 4200; Beam angle: 120°; protection class (IP): IP66; Light color: white; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 92; Amount of LED/m: 140; Severable by mm: 50; Light flux lm/m: 840; Smallest bend radius in mm: 25; Input voltage span: 24 V DC; Warranty in years: 7; Input voltage range luminaire: 24 V DC; Energy efficiency class according to EU regulation 2019/2015: F; ETIM Gruppen-ID: EC002706; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Colour of light adjustable: No width: 10mm