

PRODUCT NO. 4252-24

LED power supply unit CV 24V DC 75W 3.15A IP67



to the product page



- The LED power supply units in an IP67 aluminum housing are used for LED and lighting applications.
- Overload protection by switching off
- Suitable for constant current and constant voltage

PRODUCT GROUP	EC002710_LED-Betriebsgerät	PROTECTION CLASS (IP)	IP67
SUCCESSION ARTICLE	-	INPUT VOLTAGE	176 - 240 AC/DC
WEIGHT IN KG	0.674	INRUSH CURRENT IN A	0
POWER CONSUMPTION IN WATTS	75	TC TEMPERATURE IN °C	85
Dimensions		OUTPUT VOLTAGE	24 DC
length: 243mm		INPUT VOLTAGE SPAN	100-305 AC / 142-431 DC
width: 71mm		WARRANTY IN YEARS	5
height: 37mm		INPUT VOLTAGE RANGE LUMINAIRE	100-305 AC / 142-431 DC
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No
		DIMMING TOUCH AND DIM	No
		DIMMING ZIGBEE	No

DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	941901539
Dimension Length in mm	
DIAMETER IN MM	0
ABMESSUNGEN BREITE MM	71
ABMESSUNGEN HÖHE MM	37
Ausgangsstrom in A	