

LED power supply CV 12V DC 60W 5A IP67

Order number: 4252-12

- Power supply in aluminum housing
- Overload protection by shutdown
- IP67 protected housing
- not dimmable
- with open cable ends

Power consumption in watts: 60; protection class (IP): IP67; Input voltage: 176 - 240 V AC/DC; Output current in A: 5; Power Factor: 0,95; Inrush current in A: 0; Output voltage: 12 DC; Input voltage span: 100-305 V AC / 142-431 V DC; Input voltage range luminaire: 100-305 V AC / 142-431 V DC; ETIM Gruppen-ID: EC002710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: Yes; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany
width: 63mm