

DOTLUX Power supply for LED downlight CIRCLE 12W (Art. 2826) emergency power 300mA, flicker free

Order number: 4329

- suitable for emergency power supply
- flicker-free

Power consumption in watts: 12; protection class (IP): IP20; Input voltage: 176 - 240 V AC/DC; Output current in A: 0,3; Inrush current in A: 0; Tc temperature in °C: 80; Protection class: II; Overvoltage protection: 3750 V; Output voltage: 25 - 40 DC; Input voltage span: 180-264 V AC; Warranty in years: 5; Input voltage range luminaire: 180-264 V AC; ETIM Gruppen-ID: EC002710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: Yes; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany
width: 36mm