

PRODUCT NO. 4329

DOTLUX Power supply unit for LED downlight CIRCLE 12W (Art. 2826) suitable for emergency current 300mA, flicker-free



to the product page

- suitable for emergency power supply
- flicker-free

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 2829

WEIGHT IN KG 0.07
POWER CONSUMPTION IN WATTS 12

Dimensions

length: 96mm
width: 36mm
height: 24mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 AC/DC
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	80
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	yes
OVERVOLTAGE PROTECTION	3750 V
OUTPUT VOLTAGE	25 - 40 DC
INPUT VOLTAGE SPAN	180-264 AC
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	180-264 AC
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No

DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
CONSTANT LIGHT OUTPUT (CLO)	Yes
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
MODEL	-
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR CONSTANT CURRENT	Yes
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	941901829
DIAMETER IN MM	0
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-30-50
ABMESSUNGEN BREITE MM	36
ABMESSUNGEN HÖHE MM	24
Ausgangsstrom in A	
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	75
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	18