

PRODUCT NO. 4331-040240

DOTLUX LED table lamp STUDIodesk 80W 4000K dimmable



to the product page

- Aluminum housing in RAL9006 from the "STUDIO" series
- Integrated presence sensor activates/dims the luminaire to 30% brightness after 10 minutes and deactivates the luminaire after a further 10 minutes
- Glare-free, homogeneous and shadow-free light distribution / smooth top surface
- Better contrast rendition with very good color rendering and constant color temperature (3-step MacAdam binning)
- 1.5 m connection cable
- Emergency power supply capable
- Flicker-free light rendition ensures optimum vision, is easy on the eyes for fatigue-free working and creates a pleasant atmosphere in offices, conference rooms and hotels.

PRODUCT GROUP	EC000300_Stehleuchte		
SUCCESSION ARTICLE	4331-140240	BEAM ANGLE	120x120
WEIGHT IN KG	7	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	80	INPUT VOLTAGE	220 - 240 AC
NET LUMINOUS FLUX IN LUMENS	8800	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	110	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	110
Dimensions		PROTECTION CLASS	I
length: 610mm		VOLTAGE TYPE	AC
width: 310mm		GLARE-FREE	UGR < 19
height: 1200mm		SWITCH CYCLES	> 100.000
		INPUT VOLTAGE SPAN	220-240 AC
		WARRANTY IN YEARS	7
		L80/B10	50000
		SIMILAR TO RAL-COLOUR	9006
		DIMMING WITHOUT DIMMER	No
		ENABLED LICENSED PRODUCT	Yes
		INPUT VOLTAGE RANGE LUMINAIRE	220-240 AC
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	50000

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
WITH ILLUMINANT	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
MATERIAL COVER	Plastic matt/satinized
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	Yes
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	Yes
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM3
WITH MOVEMENT SENSOR	Yes
WITH LIGHT SENSOR	No
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
ELECTRICAL CONNECTION WITH CONNECTOR SYSTEM	No
LUMINAIRE HEADS FLEXIBLE	No
DIRECT-/INDIRECT PROPORTION SEPARATELY CONTROLLABLE	Yes
ADJUSTABLE	Nein
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	80
LAMP TYPE	LED exchangeable
WITH DIMMER	No
WITH PRESENCE INDICATOR	No
WITH REFLECTOR	No
WITH SWITCH	No

WITH SEPARATE READING LIGHT	No
MATERIAL	Aluminium
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	E
ELDAS-NR.	941700069
DIAMETER IN MM	0
MAX. SYSTEM POWER IN W	80
ABMESSUNGEN BREITE MM	310
ABMESSUNGEN HÖHE MM	1200
NOMINAL VOLTAGE IN V	48
COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
LIGHT OUTLET	Direct/indirect
LUMINOUS FLUX ADJUSTABLE	Continuously variable
TYPE OF GRID	None
HOUSING COLOUR	silver