

PRODUCT NO. 4377-24

LED outdoor power supply IP67 24V DC 480W



to the product page

- Powerful LED switching power supply 480W
- installed in robust aluminum housing
- protected against short circuit, overload, overvoltage, overtemperature

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -

WEIGHT IN KG 2.58

Dimensions

length: 262mm
width: 125mm
height: 44mm

PROTECTION CLASS (IP)	IP67
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
PROTECTION CLASS	I
SUITED FOR EMERGENCY LIGHTING	No
OUTPUT VOLTAGE	24
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	No
DIMMING 0-10 V	Yes
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No

DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
SUITABLE FOR EMERGENCY LIGHTING	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
MODEL	Static
SUITABLE FOR CONSTANT VOLTAGE	Yes
SUITABLE FOR OUTDOOR USE	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
HOUSING	Metal housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	941901649
Dimension Length in mm	
DIAMETER IN MM	0
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	40-80
ABMESSUNGEN BREITE MM	125
ABMESSUNGEN HÖHE MM	44
Ausgangsstrom in A	