

**DOTLUX LED light LUNA IP44 Ø330mm 18W COLORselect**

Order number: 2347-1FW180

3 light colors in one luminaire - The right light color can be set for every application environment.

1. warm white 3.000 K: hotel, store, wellness/spa areas, home & living
  2. neutral white 4.000 K: office, gastronomy, industry, sanitary, retirement homes and hospitals
  3. daylight white 5.700 K: Industry, meeting rooms, educational institutions, Office
- Frosted cover provides shadow-free light Distribution
  - Stable PMMA plastic cover
  - Self-cooling LED module
  - Integrated luminaire connection with pressure clamp
  - Suitable for central battery
  - Sustainable, repairable product design

Power consumption in watts: 18; Net luminous flux in lumens: max. 1950; Lumen per watt: 108; Beam angle: 180°; protection class (IP): IP44; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,5; IK protection: IK07; Lumen per watt: 108; Protection class: I; Housing colour: white; Suited for emergency lighting: No; Switch cycles: > 100.000; Warranty in years: 5; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK07; Suitable for emergency lighting: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No  
diameter: 330mm