

PRODUCT NO. 4686

External driver CIRCLEugr-dim 300mA 9W not dimmable



to the product page

- External driver for DOTLUX CIRCLEugr
- Not dimmable
- 300mA 9W

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -

WEIGHT IN KG 0.052

POWER CONSUMPTION IN WATTS 9

Dimensions

length: 95mm

width: 35mm

height: 25mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 AC
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	85
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	No
Output voltage	
INPUT VOLTAGE SPAN	200-265 AC
WARRANTY IN YEARS	3
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	200-265 AC
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
CONSTANT LIGHT OUTPUT (CLO)	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR OUTDOOR USE	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	919390189
Dimension Length in mm	
DIAMETER IN MM	0
ABMESSUNGEN BREITE MM	35
ABMESSUNGEN HÖHE MM	25
Ausgangsstrom in A	