

PRODUCT NO. 4747-030120

**DOTLUX LED wall light WALLround 25cm 14W 3000K**



to the product page

- High-quality aluminum housing with powder coating in RAL7016
- Robust, splash-proof design for outdoor use with IP 65 protection
- Glare-free, homogeneous and shadow-free light distribution
- EasyBase platform enables quick and easy installation
- Mounting accessories included
- Insect-friendly lighting thanks to warm white LEDs
- Housing color similar to RAL 7016

<b>PRODUCT GROUP</b>	EC002892_Decken-/Wandleuchte		
<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120
<b>WEIGHT IN KG</b>	1.63	<b>PROTECTION CLASS (IP)</b>	IP65
<b>POWER CONSUMPTION IN WATTS</b>	14	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	1050	<b>INPUT VOLTAGE</b>	220 - 240 AC
<b>LUMEN PER WATT</b>	75	<b>SERVICE LIFE</b>	approx. 30.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	3000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
<b>Dimensions</b>		<b>POWER FACTOR</b>	0,95
<b>length:</b> 253mm		<b>INRUSH CURRENT IN A</b>	0
<b>width:</b> 253mm		<b>IK PROTECTION</b>	IK08
<b>height:</b> 65mm		<b>LUMEN PER WATT</b>	75
<b>diameter:</b> 253mm		<b>HOUSING COLOUR</b>	gray
		<b>WARRANTY IN YEARS</b>	3
		<b>L80/B10</b>	30000
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>LIFETIME L80/B10 AT 25°C</b>	30000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	60000
		<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
		<b>MATERIAL COVER</b>	Plastic matt/satinized
		<b>TYPE OF CONTROL GEAR</b>	LED operating device current-controlled

WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM1
IMPACT STRENGTH	IK08
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED exchangeable
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	60000
LIFETIME L90/B10 AT 25°C	15000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	D
ELDAS-NR.	941200359
Dimension Length in mm	
DIAMETER IN MM	253
MAX. SYSTEM POWER IN W	14
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-40
ABMESSUNGEN BREITE MM	253
ABMESSUNGEN HÖHE MM	65
NOMINAL VOLTAGE IN V	230
LIGHT OUTLET	Direct
TYPE OF WIRING	Suitable for through wiring
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No

**BEAM ANGLE**

Extreme wide beam >80°