

DOTLUX LED panel FLATevo 620x620mm max. 36W UGR<19 4000K

Order number: 4826-040120

- LED recessed luminaire with CDP Nano microprismatic diffuser for glare-free light distribution
- UGR<19 suitable for VDU workstations
- Low-current LEDs in conjunction with large-area rear cooling guarantee long LED service life and consequently low maintenance Costs

Power levels with different ballasts:

40W @ 1050 mA

36W @ 950 mA

27W @ 700 mA

20W @ 500 mA

14W @ 350 mA

This product is not compatible with our mounting frame 2039.

Power consumption in watts: 36; Net luminous flux in lumens: 4320; Lumen per watt: 120; Beam angle: 90°; protection class (IP): IP40; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Inrush current in A: 0; IK protection: ; Lumen per watt: 120; Protection class: III; Housing colour: white; Glare-free: UGR < 19; Switch cycles: > 100.000; Warranty in years: 5; Housing material: steel, powder-coated; Assortment: Proline; ETIM Gruppen-ID: EC002892; Dimming depending on control gear: Yes; Impact strength: IK02; Pulse duration in µs: 0; Surface protection housing: Powder coating
width: 620mm