

DOTLUX LED lamp LUNAE27-sensor 1xE27 Ø330 IP44 with sensor

Order number: 4839-0E27

- Classic design with stable PMMA plastic cover.
- Mounting on existing drill holes possible (two- or three-hole mounting from 100 to 220 mm hole spacing / Ø) due to universal perforation with longitudinal slots on the base plate. Additional 3-hole mounting with keyholes Ø 260 mm
- Ex works equipped with plug-in E27 socket, which can then be replaced with a more powerful QUICK-FIX module almost without tools (2 screws).
- When using the QUICK-FIX light module, a luminaire is created with a tool-free replaceable LED module
- Compatible with all E27 light sources and connector for QUICK-FIX up to 24 W
- Suitable for use with E27 LED light sources up to 12 W
- Sustainable product design due to easily replaceable components
- Integrated sensor with On/Off function and daylight detection
- following values are adjustable in steps
 - Range (up to 6m)
 - Daylight sensor
 - Light duration

Installation depth in mm: 0; Installation opening width in mm: 0; Installation opening length in mm: 0; Warranty in years: 5; Assortment: Proline; ETIM Gruppen-ID: E0000414; Suitable for high voltage luminaires: Yes; Suitable for lamp power in w: 20; Suitable for low voltage luminaires: No; With space for gear: Yes; BEG funding: Only relevant in Germany; Application: For slab ceiling; Material: Other
diameter: 330mm