

PRODUCT NO. 4839-0E27

**DOTLUX LED light LUNAE27-sensor 1xE27 Ø330 IP44 with sensor**



to the product page



- Classic design with sturdy PMMA plastic cover
- Can be mounted on existing drill holes (two- or three-hole mounting from 100 to 220 mm hole spacing / Ø) thanks to universal perforation with longitudinal slots on the base plate. Additional 3-hole mounting with keyholes Ø 260 mm
- Fitted ex works with plug-in E27 socket, which can then be replaced almost without tools (2 screws) with a powerful QUICK-FIX LED light.
- Tool-free replacement with the luminaire-in-luminaire system
- Compatible with all E27 light sources and connection plug for QUICK-FIX up to 24 W
- Suitable for use with E27 LED light sources up to 12 W
- Sustainable product design thanks to easily replaceable components
- Integrated sensor with on/off function and daylight detection
- The following values can be adjusted in stages:
  - Reach range (up to 6m)
  - Daylight sensor
  - Light duration

<b>PRODUCT GROUP</b>	EC000414_Leuchteneinbaugehäuse		
<b>SUCCESSION ARTICLE</b>	-	<b>INSTALLATION OPENING WIDTH IN MM</b>	0
		<b>INSTALLATION OPENING LENGTH IN MM</b>	0
<b>WEIGHT IN KG</b>	0.56	<b>WARRANTY IN YEARS</b>	5
		<b>ASSORTMENT</b>	Proline
		<b>APPLICATION</b>	For slab ceiling
<b>Dimensions</b>		<b>SUITABLE FOR HIGH VOLTAGE LUMINAIRES</b>	Yes
<b>length:</b> 330mm		<b>SUITABLE FOR LAMP POWER IN W</b>	20
<b>width:</b> 330mm		<b>SUITABLE FOR LOW VOLTAGE LUMINAIRES</b>	No
<b>height:</b> 95mm		<b>WITH SPACE FOR GEAR</b>	Yes
<b>diameter:</b> 330mm		<b>BEG FUNDING</b>	Only relevant in Germany
		<b>ELDAS-NR.</b>	920000029
		Dimension Length in mm	
		<b>DIAMETER IN MM</b>	330
		<b>ABMESSUNGEN BREITE MM</b>	330
		<b>ABMESSUNGEN HÖHE MM</b>	95
		<b>INSTALLATION HEIGHT/DEPTH IN MM</b>	0
		<b>MATERIAL</b>	Other