

DOTLUX TRUEcolor tester

Order number: 4516-1

Inspire your customers on site with vibrant and high-contrast colors. With TRUE-COLOR technology from DOTLUX, you can showcase products simply and authentically.

protection class (IP): other; Color temperature in Kelvin: 3000/4000/5700; Power Factor: 0,9; Protection class: none; Voltage type: DC; L80/B10: 0; Dimming without dimmer: No; Energy efficiency class according to EU regulation 2019/2015: -; Lifetime L80/B10 at 25°C: 0; Lifetime L80/B20 at 25°C: 0; ETIM Gruppen-ID: EC000996; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Connection type: Cable; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Flexible: Nein; Suitable for traffic lights: No; External driver required: Yes; Suitable for constant voltage: Yes; Suitable for general lighting: Yes; Suitable for constant current: No; Suitable for rail traffic: No; Suitable for matrix information boards: No; Suitable for variable road signs: No; Lifetime L90/B10 at 25°C: 0; Light colour according to EN 12464-1: neutral white 3300 to 5300 K; Lifetime L90/B50 at 25°C: 0; BEG funding: Only relevant in Germany; LED-Betriebsstrom in mA: 300; Shape: Rectangular; Photobiological safety according to EN 62471: Other; Colour: White