

PRODUCT NO. 4940

DOTLUX LED power supply QUICK-FIXadapt CC 500mA sensor



to the product page

- RADARSENSOR power supply unit incl. magnetic attachment
- Adjustable on the power supply unit
- Three different sensor functions possible
- ON/OFF function to 100% luminosity via sensor, then 0% luminosity
- ON/OFF function to 100% luminosity via sensor with adjustable afterglow duration
- Permanent basic brightness (20%) with additional ON/OFF function to 100% luminosity via sensor with adjustable afterglow duration

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -

WEIGHT IN KG 0.13

Dimensions

height: 41mm
diameter: 82mm
length: 82mm
width: 82mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 AC
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	85
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	No
OUTPUT VOLTAGE	24 - 42 DC
INPUT VOLTAGE SPAN	220-240 AC
WARRANTY IN YEARS	3
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	220-240 AC
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
SUITABLE FOR EMERGENCY LIGHTING	No
CONSTANT LIGHT OUTPUT (CLO)	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
MODEL	Static
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	No
SUITABLE FOR CONSTANT CURRENT	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ELDAS-NR.	919391249
DIAMETER IN MM	82
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20+45
ABMESSUNGEN BREITE MM	82
ABMESSUNGEN HÖHE MM	41
Ausgangsstrom in A	
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	89
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	133