

**Light management system LED power supply unit 38Watt 350mA DALI DT8 dimmable**

Order number: 4934-350

- Independent dimmable two-channel DALI DT8 LED driver
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- colorSWITCH - setting the color temperature via push-button
- Tunable White applications

protection class (IP): IP20; Input voltage: 176 - 240 V AC/DC; Service life: ; Output current in A: 0,35; Minimum load in watt: 7; Output of power supply unit: 38 W; Inrush current in A: 26.4; Tc temperature in °C: 75; Output voltage: 20 - 50 DC; Input voltage span: 198-264 V AC; Housing material: Polycarbonate; Stand by losses: < 0,25 W; Input voltage range luminaire: 198-264 V AC; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002710; Dimming DALI: Yes; No dim function: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Pulse duration in µs: 224; Cord length: 20 cm; BEG funding: Only relevant in Germany  
width: 70mm diameter: 75mm