

PRODUCT NO. 4934-950

**Light management system LED power supply unit 38Watt 950mA DALI DT8 dimmable**



to the product page

- Independent dimmable two-channel DALI DT8 LED driver
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- colorSWITCH - setting the color temperature via push-button
- Tunable White applications

**PRODUCT GROUP** EC002710\_LED-Betriebsgerät

**SUCCESSION ARTICLE** -  
**PREDECESSOR ARTICLE** 4184-900

**WEIGHT IN KG** 0.241

**Dimensions**

**length:** 215mm  
**width:** 70mm  
**height:** 31mm

|  |                 |
|--|-----------------|
| <b>PROTECTION CLASS (IP)</b>                     | IP20            |
| <b>INPUT VOLTAGE</b>                             | 176 - 240 AC/DC |
| <b>INRUSH CURRENT IN A</b>                       | 26.4            |
| <b>TC TEMPERATURE IN °C</b>                      | 75              |
| <b>OUTPUT VOLTAGE</b>                            | 20 - 40 DC      |
| <b>INPUT VOLTAGE SPAN</b>                        | 198-264 AC      |
| <b>WARRANTY IN YEARS</b>                         | 5               |
| <b>DIMMING WITHOUT DIMMER</b>                    | No              |
| <b>INPUT VOLTAGE RANGE LUMINAIRE</b>             | 198-264 AC      |
| <b>DIMMING 0-10 V</b>                            | No              |
| <b>DIMMING 1-10 V</b>                            | No              |
| <b>DIMMING DALI</b>                              | Yes             |
| <b>DIMMING DMX</b>                               | No              |
| <b>DIMMING DSI</b>                               | No              |
| <b>DIMMING LINESWITCH</b>                        | No              |
| <b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b> | No              |
| <b>DIMMING MAINS VOLTAGE MODULATION</b>          | No              |
| <b>DIMMING PROGRAMMABLE</b>                      | No              |
| <b>DIMMING RF</b>                                | No              |
| <b>DIMMING SINE WAVE REDUCTION</b>               | No              |
| <b>DIMMING TOUCH AND DIM</b>                     | No              |
| <b>DIMMING ZIGBEE</b>                            | No              |
| <b>DIMMING WITH PUSH-BUTTON</b>                  | No              |

|  |                          |
|--|--------------------------|
| <b>NO DIM FUNCTION</b>                     | No                       |
| <b>OPERATION BY BLUETOOTH</b>              | No                       |
| <b>COMPATIBLE WITH CASAMBI</b>             | No                       |
| <b>COMPATIBLE WITH APPLE HOMEKIT</b>       | No                       |
| <b>COMPATIBLE WITH GOOGLE ASSISTANT</b>    | No                       |
| <b>COMPATIBLE WITH AMAZON ALEXA</b>        | No                       |
| <b>IFTTT SUPPORT AVAILABLE</b>             | No                       |
| <b>HOUSING</b>                             | Plastic housing          |
| <b>DIMMING GPRS</b>                        | No                       |
| <b>PULSE DURATION IN <math>\mu</math>S</b> | 224                      |
| <b>BEG FUNDING</b>                         | Only relevant in Germany |
| <b>ELDAS-NR.</b>                           | 941934109                |
| Dimension Length in mm                     |                          |
| <b>DIAMETER IN MM</b>                      | 0                        |
| <b>ABMESSUNGEN BREITE MM</b>               | 70                       |
| <b>ABMESSUNGEN HÖHE MM</b>                 | 31                       |
| Ausgangsstrom in A                         |                          |