

PRODUCT NO. 4941-950

Light management system LED power supply unit 38Watt 950mA CASAMBI dimmable



to the product page

- Independent dimmable dual-channel CASAMBI LED driver
- Automatically establishes a wireless communication network with up to 127 nodes
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- Tunable White applications

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -

WEIGHT IN KG 0.25

Dimensions

length: 215mm
width: 70mm
height: 31mm
diameter: 75mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 AC/DC
INRUSH CURRENT IN A	26.4
TC TEMPERATURE IN °C	75
OUTPUT VOLTAGE	20 - 40 DC
INPUT VOLTAGE SPAN	198-264 AC
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	198-264 AC
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	Yes
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No

COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR OUTDOOR USE	No
HOUSING	Plastic housing
DIMMING GPRS	No
PULSE DURATION IN μS	224
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	919391439
DIAMETER IN MM	75
ABMESSUNGEN BREITE MM	70
ABMESSUNGEN HÖHE MM	31
Ausgangsstrom in A	