

PRODUCT NO. 4989

CASAMBI LED power supply 1-38Watt 300-1050mA dimmable



to the product page



- Control via smartphone using the CASAMBI APP
- Integrated connection for manual dimming via push-button
- Amplitude dimming for absolutely flicker-free light at every dimming level 1-100%
- MADE in EU

PRODUCT GROUP EC002710_LED-Betriebsgerät

WEIGHT IN KG 0.144

Dimensions

length: 147mm

width: 44mm

height: 30mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 AC/DC
POWER FACTOR	0,99
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	80
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	No
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Yes
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	Yes
DIMMING SINE WAVE REDUCTION	No

DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	Yes
NO DIM FUNCTION	No
SUITABLE FOR EMERGENCY LIGHTING	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	Yes
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
MODEL	Dynamic
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	No
SUITABLE FOR CONSTANT CURRENT	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	919391469
Dimension Length in mm	
DIAMETER IN MM	0
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	25-45
ABMESSUNGEN BREITE MM	44
ABMESSUNGEN HÖHE MM	30
Ausgangsstrom in A	