


PRODUCT NO. 4993-0FW140

DOTLUX LED mirror light TRENDO 10W 3000/4000/5700K COLORselect



to the product page

- Modern, stylish design
- Maximum illuminated area without visible screw connections
- EASYbase platform enables quick and easy installation
- Mounting on existing drill holes possible due to free surface on the base plate
- 2 cable inlets pre-installed (individual inlets can be drilled into the aluminum base if required)
- Simply set your desired light color yourself, one article number - three light colors through COLORselect
- Sustainable product design thanks to easily replaceable components

PRODUCT GROUP EC002892_Decken-/Wandleuchte

SUCCESSION ARTICLE -

WEIGHT IN KG 0.64
POWER CONSUMPTION IN WATTS 10
NET LUMINOUS FLUX IN LUMENS 1200
LUMEN PER WATT 120

Dimensions

length: 600mm
width: 85mm
height: 57mm

BEAM ANGLE 140
PROTECTION CLASS (IP) IP44
LIGHT COLOR white
INPUT VOLTAGE 186 - 240 AC/DC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 3000/4000/5700
COLOR-RENDERING-INDEX CRI > 82
POWER FACTOR 0,95
INRUSH CURRENT IN A 0
LUMEN PER WATT 120
PROTECTION CLASS I
VOLTAGE TYPE AC/DC
HOUSING COLOUR multicoloured
SUITED FOR EMERGENCY LIGHTING No
GLARE-FREE UGR < 25
SWITCH CYCLES > 100.000
INSTALLATION OPENING WIDTH IN MM 0
INSTALLATION OPENING LENGHT IN MM 0
INPUT VOLTAGE SPAN 240
WARRANTY IN YEARS 5
L80/B10 50000
SUITABLE FOR SURFACE MOUNTING Yes
SUITABLE FOR MOUNTING No
INPUT VOLTAGE RANGE LUMINAIRE 240

ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
MATERIAL COVER	Plastic matt/satinized
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT SHARING	-
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM4
IMPACT STRENGTH	IK08
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	No
TYPE OF WIRING	Ending
CONNECTION TYPE	Other open cable ends
COLOUR OF LIGHT ADJUSTABLE	Positions

OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	10
LAMP TYPE	LED exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	C
ELDAS-NR.	941200539
DIAMETER IN MM	0
MAX. SYSTEM POWER IN W	10
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-45
ABMESSUNGEN BREITE MM	85
ABMESSUNGEN HÖHE MM	57
INSTALLATION HEIGHT/DEPTH IN MM	0
NOMINAL VOLTAGE IN V	230
LIGHT OUTLET	Direct
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
TYPE OF GRID	None
LIGHT DISTRIBUTOR	Other
SURFACE PROTECTION HOUSING	Other
BEAM ANGLE	Extreme wide beam >80°
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	Other